



## NOTES:

1. ASSEMBLED CONNECTOR INTERFACE IS DESIGNED IN ACCORDANCE WITH MIL-STD-348.

2. MATERIAL: GASKET - SILICONE RUBBER PER ZZ-R-765

INSULATOR - TEFLON PER ASTM D1710

CONTACT - BERYLLIUM COPPER PER ASTM B196. ALL OTHER METAL PARTS - BRASS PER ASTM B16.

UNLESS OTHERWISE SPECIFIED: TOLERANCES: 3 PLACES = ±.005, 2 PLACES = ±.02, ANGLES = ±1/2\*, SURFACE FINISH

BUSHING - BRASS PER ASTM B16.

3. FINISHES: CONTACT - SILVER PLATE PER QQ-S-365 ALL OTHER METAL PARTS - NICKEL PLATE PER QQ-N-290

		-	OUTLINE	4/21/05	В
-	63	ALT.	REVISIONS	DATE	D.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS MFG CORP. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

UG-60E/U

DELTA	ELECTRONICS	MFG.	CORP.	Beverly,	MA	01915
TITLE.						

HN CLAMP JACK FOR RG-8A 9B, 87A, 213, 214 & 225/U CABLES

Drawn by BJM 4/21/05	Scale 2/1	Ckd. by MR	Engr Appd MR	FILE NAME: 1608004N000-000T

CODE IDENT.-00795 | 1608-004-N000